









KEY FEATURES



Machine Control Panel uses off-the-shelf toggle and marine duty switches and features universal icons which simplifies



Vacuum Muffler allows machine to consistently achieve as low as 62 dB while thoroughly drying the floor.



EDGE Orbital Scrubhead delivers premier chemical-free floor stripping while reducing water consumption by up to 70%.



Squeegee Adjustments made simple with quick change squeegee latch allows toolless maintenance and 4-sided squeegee blade.



Front Fill System features a retractable hose for easy filling on standard sink-faucets.





High Performance motors and down pressure provides an unmatched standard of cleaning.







APPLICATIONS

School Systems

Healthcare

Warehouses

Grocery Stores

Retail


Automotive

Food Packaging

Airports

Sports Arenas






EASE OF MAINTENANCE

- 1 Tip Back "Clam Shell" Design
- 2 Access to Batteries
- 3 Access to Scrub Motors
- 4 Access to Solution Filter
- 5 White Vacuum Filter Access
- 6 Full Recovery Tank Access

VIEW INSIDE




THREE SCRUB SYSTEMS TO CHOOSE FROM

Corner Rollers Non-Marking HD Motors Better Performance Corner Rollers Non-Marking Thick Steel Design 1/4" Thick for Durability Aluminum Deck Design Corrosion Resistance Oversized Brushes (6") Longer Life

BENEFITS

- Brush / Pad Selection
- Lowest Maintenance Cost
- Gimballed Drivers Improves Cleaning On Irregular Floors
- Brushes Individually Driven For Unmatched Performance


CYLINDRICAL



BENEFITS

- Eliminates Dust Mopping
- Scrub & Sweep Simultaneously
- Superior Grouted Tile Cleaning

EDGE



BENEFITS

- Chemical Free Stripping
- Reduce Slip & Fall Potential
- Earn LEED Credits
- 70% Reduction in Water Usage
- Consistent Results No Swirl Marks
- Wet screens Wood Gym floors

CALL FOR A DEMONSTRATION

800-450-9824

(+001)-262-681-6470

www.tomcatequip.com

Since 1986, our family owned company has been designing, building and supporting the best in floor maintenance equipment. Our **Tomcat** brand services the world with unsurpassed commercial cleaning equipment, continually exceeding expectations and setting the industry bar that much higher.

We've built our reputation by providing the highest value machines and providing local support via 425 distributors in over 42 different countries.

AUTHORIZED DISTRIBUTOR

BODY CONSTRUCTION / DIMENSIONS

Tank Material: Poly 3/8" (10 mm)

3/16" (5 mm) Powder Coated Steel Chassis Construction:

Front Wheels (Diameter × Width): (2x) 10" x 2.5" ([2x] 25 x 6 cm) - Non-Marking Solid Grey

Rear Casters (Diameter × Width): (2x) $4'' \times 2''$ ([2x] 10×5 cm) - Non-Marking Grey

Size $(L \times W \times H)$: $52" \times 22" \times 40"$ (132 × 56 × 102 cm)

Weight (w/o Batteries): 393 - 443 lbs (178 - 201 kg) Weight (w/ 210 ah Batteries): 625 - 675 lbs (284 - 306 kg)

BRUSH / PAD SYSTEM

Disk Dimensions: 26" - (2x) 13" Diameter (66 - [2x] 33 cm) Includes Jaws with Rollers for Wall Protection 28" - (2x) 14" Diameter (71 - [2x] 36 cm) (2x) 0.75 hp / 270 rpm ([2x] 559 watts) Disk Motor:

Optional Motor Upgrade: (2x) 1.0 hp / 350 rpm ([2x] 746 watts)

Disk Brush Speed: 270 rpm or 350 rpm

Cylindrical Dimensions: 25" - (2x) 6" \times 23" (63.5 - [2x] 15×58 cm) 6" Diameter Brush 29" - $(2\times)$ 6" \times 27" $(73.7 - [2\times] 15 \times 69 \text{ cm})$ Cylindrical Motor: 25" - (2×) 0.75 hp / 350 rpm ([2×] 559 watts)

29" - (2x) 1.0 hp / 350 rpm ([2x] 746 watts) Cylindrical Brush Speed: 750 rpm

 $24" \times 14" (70 \times 36 cm)$ **EDGE Dimensions:** $28" \times 14" (71 \times 36 cm)$

EDGE Motor: 1.0 hp / 2500 rpm (746 watts) EDGE Optional HD Motor: 1.2 hp / 2900 rpm (894 watts)

Scrub Pressure Actuator Rating: 500 lbs (227 kg) **Brush Pressure Settings:** (5) with Auto Adjust

POWER SYSTEM

System Voltage: 24 VDC Standard Battery: 210 ah WET

245 ah WET / 250 ah AGM* Optional Battery:

*Includes Onboard Charger

Run Time: Up to 3.5 Hours**

**Run times are based on continuous scrubbing run time

Charger: 120VAC / 60 Hz Input - 24VDC / 25 amp Output

DRIVE SYSTEM:

Power: 0.75hp - All Gear / Sealed (559 watts)

0 - 290 ft/min / 0 - 3.3 mph (0 - 88 m/min / 0 - 5 km/h) Forward Speed: Scrubbing Speed: 0 - 229 ft/min / 0 - 2.6 mph (0 - 70 m/min / 0 - 4 km/h) Reverse Speed: 0 - 202 ft/min / 0 - 2.3 mph (0 - 62 m/min / 0 - 4 km/h)

SOLUTION / RECOVERY SYSTEMS:

Solution Tank Capacity: 16 Gallons (61 liters) - w/ Graduated Site Tube XL Tank Option Solution Capacity: 21 Gallons (80 liters) - w/ Graduated Site Tube

Solution Flow / Filter: 0 - 0.7 GPM / Stainless Inline (0 - 2 LPM)

Recovery Tank Capacity: 17 Gallons (64 liters) - 1.5" diameter Drain Hose 23 Gallons (87 liters) - 1.5" diameter Drain Hose XL Tank Option Recovery Capacity:

Demisting Chamber: 1.25 Gallons (5 liters) Drain Saver: 30 cubic inches (492 cubic cm)

0.8 hp / 3 Stage (640 watts) Vacuum Power: Vacuum Specs (Water Lift / Airflow): 68" / 72 cfm (173 cm / 2 cm/m)

36" Curved w/ 4-sided Rear Blade & Quick Change Latch $\ensuremath{\textit{Optional}}$ - 42" Squeegee Squeegee:

GENERAL:

Cleaning Width: 26" & 28" - Disk (66 & 71 cm)

25" & 29" - Cylindrical (64 & 74 cm) 24" & 28" - EDGE (70 & 71 cm)

Decibels: 62 dB

Productivity - Theoretical: Up to 27,027 sqft (2,511 sqm)***

***Productivity is based off of ISSA 2010 Cleaning Times

Productivity - Practical: Up to 12,526 sqft (1,164 sqm)*** ***Productivity is based off of ISSA 2010 Cleaning Times

www.tomcatequip.com Copyright R.P.S. Corporation 2016. All rights reservations our policy is one of constant improvement, all specifications are subject to change without notice

International: (+001) 262-681-6470

1711 South Street Racine, Wisconsin 53404 (USA) Phone: (800) 450-9824

Manufactured By:

R.P.S. Corporation